

Specifications

备注(Remark)


1. 材料(MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色
Housing: PA6T+30%G.F UL94V-0, Color: Black
四方针: 黄铜



Contact :Brass

2. 特性 (characteristics):

额定电流: 3 AMP
额定电压: 500V.
接触电阻: 20 mΩ MAX.
接触电阻: 20 mΩ MAX.
绝缘电阻: 1000 MΩ min.
绝缘电阻: 1000 MΩ min.
耐压: AC 500V.
绝缘电压: AC 500V.
温度范围: -40°C to +105°C
温度范围: -40°C to +105°C



Recommended P, C, B layout



Ordering Information

3PXXM- 21 XX XX X XXX X 1 Δ

Plastics	No. of Pins	Contact Plating	Insulator	Length	Packing
Height	Per Row	Material	Material	mm	
10: H=1.0	2 40P	G=Gold	M=Polyimide	96	A: PE Bag
15: H=1.5		G=50" Gold	B: P85T		B: Tape & Reel
17: H=1.7		G=50" Gold	C: P85T		C: Tube
20: H=2.0		G=50" Gold	D: LCP		D: Tube-CAP
25: H=2.54		G=50" Gold			E: Tray
		G=50" Gold			F: Tape & Reel
		P=50" Gold			
		F=10" Gold/Tin			
		F=50" Gold/Tin			
		F=100" Gold/Tin			
		F=150" Gold/Tin			
		F=200" Gold/Tin			
		Sn=Sn			
		Sn=Matte Tin			

Dimension antitheses list

ITEM	B	H	D
Standard	6.0	1.0 1.5 1.7 2.0 2.54	0 1.2
Alternate			

LARCON 连润电子有限公司
Lrcon Electronics Co., Ltd

PART NO.	3PXXM-21XXXXXXX1
TITLE:	2.54双排针 SMT
Customer No.	

SCALE		Fit
UNIT		MM
SIZE	A4	DESIGN
SHEET	1/1	CHECK
PROJ.		APPROVE

LI	AN	DR	OP	SCALE	UNIT
张涛	DESIGN	张涛	DESIGN	张涛	DESIGN
罗荣军	CHECK	罗荣军	CHECK	罗荣军	CHECK
方里军	APPROVE	方里军	APPROVE	方里军	APPROVE

OPERATION	SCALE	UNIT
X.X ±0.40	A4	DESIGN
X.XX ±0.25	1/1	APPROVE
X.XXX ±0.15	1/1	APPROVE
Angle ±3°	1/1	APPROVE
DIM	1/1	APPROVE

CHANGE	APPROVE	SCALE	UNIT
CHANGE	APPROVE	张涛	DESIGN
CHANGE	APPROVE	罗荣军	CHECK
CHANGE	APPROVE	方里军	APPROVE

MODIFICATION DESCRIPTION	SCALE	UNIT
NEW	A4	DESIGN
NEW	1/1	APPROVE
NEW	1/1	APPROVE

DATE	SCALE	UNIT
20/06/09	A4	DESIGN
12/05/18	1/1	APPROVE
12/05/18	1/1	APPROVE

REV	SCALE	UNIT
1	A4	DESIGN
2	1/1	APPROVE
3	1/1	APPROVE

DATE	SCALE	UNIT
20/06/09	A4	DESIGN
12/05/18	1/1	APPROVE
12/05/18	1/1	APPROVE