

HSF RoHS

1. 材料(MATERIAL)

- 胶芯: PBT/PA6T+30%GF UL94V-0, 颜色: 黑色

端子: 黄铜/磷青铜

2. 特性 (characteristics):

Rating Current: 3 AMP.








Contact Resistance: 20 mΩ MAX.

Insulating Resistance: 10

Withstanding Voltage: AC 500V.

Temperature Range: -40 C to +105 C

Ordering Information

3F85S- 11 XX XX X Y X 1 Δ_{A1} 

Recommended P.C.B layout



LARCON
连润电子有限公司
Larcon Electronics Co., Ltd.

A1	20/06/09	Improve numbering instructions (完善编号注释说明)		张涛	X.XX	±0.25	罗荣军	CHECK	罗荣军	SIZE	A4	DESIGN	PART NO.	3F85S-11XXXXXXVY1
A0	12/05/18	NEW	————	————	X.XXX	±0.15	罗荣军	CHECK	罗荣军	SHEET	1/1	CHECK	TITLE:	2.5φ单排母 塑高8.5 180度 Y型
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL	APPROVE	方里军	PROJ.	APPROVE	Customer No.			