

Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色

Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 黄铜/磷青铜

Contact : Brass/Phosphor bronze

2. 特性 (Characteristics):

额定电流: 3 AMP

接触电阻: 20 mΩ MAX.

绝缘电阻: 1000 MΩ min.

绝缘耐压: AC 500V.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.


温度范围: -40°C to +105°C

Temperature Range: -40°C to +105°C



Ordering Information

3F85M- 21 XX XX X 0 X 1 Δ

No. of Pins Per Row 2-40P	Contact Plating G=10" Gold G=30" Gold G=50" Gold G=100" Gold G=150" Gold G=300" Gold F=10" Gold/Tin F=30" Gold/Tin F=50" Gold/Tin F=100" Gold/Tin F=150" Gold/Tin F=300" Gold/Tin Sn= Tin S= Matte Tin	Insulator Material D: PA6T C: PA9T D: LCP	Packing A: PE Bag B: Tape & Reel+CAP C: Tube D: Tube+CAP E: Tray F: Tape & Reel
---------------------------------	--	---	---



Recommended P.C.B layout



		连润电子有限公司		Lrcon Electronics Co., Ltd	
		Lrcon		3F85M-21XXXXX0X1	
A1	20/06/09	Improve numbering instructions (完善编号标注说明)	Δ	张涛	张涛
A0	12/05/18	NEW			
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Customer No.
1	2	3	4	5	6
6	7	8	9	10	
		Fit		MM	
		SCALE		UNIT	
		SIZE		A4	
		SHEET		1/1	
		PROJ.		APPROVE	
		TITLE:		2.54双排母 塑高8.5 SMT 0型	
		PART NO.		3F85M-21XXXXX0X1	
		Customer No.			