

Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色
Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 黄铜/磷青铜

Contact : Brass/Phosphor bronze

2. 特性 (Characteristics):

额定电流: 2 AMP

接触电阻: 20 mΩ MAX.

绝缘电阻: 1000 MΩ min.

耐压: AC 500V.

温度范围: -40°C to +105°C

Withstanding Voltage: AC 500V.

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

Ordering Information

2F40M- 21 XX XX X 0 X 1 Δ

No. of Pins Per Row 2/40P	Contact Plating Material	Insulator Material	Packing
G=10" Gold	G=10" Gold	D: PA6T	A: PE Bag
G=30" Gold	G=30" Gold	C: PA6T	B: Tape & Reel+CAP
G=50" Gold	G=50" Gold	D: LCP	C: Tube
G=100" Gold	G=100" Gold		D: Tube+CAP
G=150" Gold	G=150" Gold		E: Tray
G=300" Gold	G=300" Gold		F: Tape & Reel
F=10" Gold/Tin	F=10" Gold/Tin		
F=30" Gold/Tin	F=30" Gold/Tin		
F=50" Gold/Tin	F=50" Gold/Tin		
F=100" Gold/Tin	F=100" Gold/Tin		
F=150" Gold/Tin	F=150" Gold/Tin		
F=300" Gold/Tin	F=300" Gold/Tin		
Sn=Sn	Sn=Sn		
Sn=Matte Tin	Sn=Matte Tin		

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	ANGLE	TOL	APPROVE	OPERATION	DRAW	LI	ANR	SCALE	UNIT	Fit
A1	20/06/09	Improve numbering instructions (完善编号标注说明)	Δ	张涛	X.X	±0.40		DESIGN	张涛	DESIGN	张涛	张涛	MM		
A0	12/05/18	NEW			X.XX	±0.25		CHECK	罗荣军	CHECK	罗荣军	罗荣军	A4	SIZE	
					X.XXX	±0.15		SHEET		1/1			CHECK		
					Angle	±3°		PROJ.		APPROVE			APPROVE		