



Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色

Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 黄铜/磷青铜

Contact : Brass/Phosphor bronze

2. 特性 (Characteristics):

额定电流: 1 AMP

Current Rating: 1 AMP.

接触电阻: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘电阻: 1000 MΩ min.

Insulating Resistance: 1000 MΩ min.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.


温度范围: -40°C to +105°C

Temperature Range: -40°C to +105°C


Ordering Information

1F46S- 21 XX XX X Y X 1 Δ

No. of Pins Pin 9, low 2 30°	Contact Plating G: Gold Flash G1=10" Gold G2=30" Gold G3=50" Gold G4=100" Gold G5=150" Gold G6=300" Gold F: 10" Gold/Tin F1=30" Gold/Tin F2=50" Gold/Tin F3=100" Gold/Tin F4=150" Gold/Tin F5=300" Gold/Tin Sn= Tin Sn= Matte Tin	Insulator Material D: PA6T C: PA9T D: LCP	Insulator A: PE Bag B: Tape & Reel+CAP C: Tube D: Tube+CAP E: Tray F: Tape & Reel	Packing
------------------------------------	--	---	---	---------



Recommended P.C.B layout



DIM"A" 1.60 2.40 3.00

LIRCON 连润电子有限公司
Lrcon Electronics Co., Ltd

A1	20/06/09	Improve numbering instructions (完善编号标注说明)	张涛	DESIGN	张涛	UNIT	MM	Fit
A0	12/05/18	NEW	张涛	CHECK	罗荣军	SIZE	A4	DESIGN
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	APPROVE	SHEET	1/1	CHECK
						PROJ.	1.27双排母 塑高4.6 180度 Y型	APPROVE
								Customer No.